Criteria Air Pollutant Emissions Calculations

Number of Daily Vehicle Trips	62
Maximum Daily VMT	1014

Pollutant	Emission Factor Type	Emiss	ion Factor	Daily Emissions (grams/day)	Daily Emissions (lbs/day)
	RUNEX	0.041275223	grams/mile	41.85	0.0922
	IDLEX ¹	0	grams/vehicle/day	0.00	0.0000
	STREX	0.490113042	grams/trip	30.39	0.0669
ROG	HOTSOAK	0.237161457	grams/trip	14.70	0.0324
noc	RUNLOSS	0.865214339		53.64	0.1182
	RESTLOSS		grams/vehicle/day	12.01	0.0264
	DIURN	0.473624501	grams/vehicle/day	14.68	0.0323
				TOTAL	0.3685
	RUNEX	0.152815038	grams/mile	154.95	0.3413
NO_x	IDLEX ¹	0	grams/vehicle/day	0.00	0.0000
ΝΟχ	STREX	0.329095635	grams/trip	20.40	0.0449
				TOTAL	0.3863
	RUNEX	1.620705972	grams/mile	1643.40	3.6198
со	IDLEX ¹	0	grams/vehicle/day	0.00	0.0000
co	STREX	2.825834995	grams/trip	175.20	0.3859
				TOTAL	4.0057
	RUNEX	0.003440971	grams/mile	3.49	0.0077
SO _x	IDLEX ¹	0	grams/vehicle/day	0.00	0.0000
SO _χ	STREX	0.000688433	grams/trip	0.04	0.0001
				TOTAL	0.0078
	RUNEX	0.00283291	grams/mile	2.87	0.0063
	IDLEX ¹	0	grams/vehicle/day	0.00	0.0000
DNA	STREX	0.002924334	grams/trip	0.18	0.0004
PM_{10}	PMTW	0.008000002	grams/mile	8.11	0.0179
	PMBW	0.036750011	grams/mile	37.26	0.0821
				TOTAL	0.1067
	RUNEX	0.00260495	grams/mile	2.64	0.0058
	IDLEX ¹	0	grams/vehicle/day	0.00	0.0000
DIV	STREX	0.002689121		0.17	0.0004
PM _{2.5}	PMTW	0.002000001	grams/mile	2.03	0.0045
	PMBW	0.015750005	grams/mile	15.97	0.0352
				TOTAL	0.0458

Notes

VMT = vehicle miles traveled; ROG = reactive organic gases; NO_X = nitrogen oxides; CO = carbon monoxide; SO_X = sulfur oxides; PM_{10} = particulate matter measuring no more than 10 microns in diameter; $PM_{2.5}$ = particulate matter measuring no more than 2.5 microns in diameter; $PM_{2.5}$ = Running Exhaust Emissions; $PM_{2.5}$ = Diurnal Evaporative Hydrocarbon Emissions; PM_X = Start Exhaust Tailpipe Emissions; PM_X = Hot Soak Evaporative Hydrocarbon Emissions; PM_X = Running Loss Evaporative Hydrocarbon Emissions; PM_X = Tire Wear Particulate Matter Emissions; PM_X = Brake Wear Particulate Matter Emissions

Emissions factor source: California Air Resources Board EMFAC2017 Web Database v. 1.0.2 Emission Rates for Monterey County for year 2020 for gasoline-fueled LDT1 vehicles.

More information on emission factors can be found in the EMFAC2017 Volume I - User's Guide (2018) available at: https://ww3.arb.ca.gov/msei/downloads/emfac2017-volume-i-users-guide-final.pdf

¹ According to the CARB EMFAC 2017 Volume 1 - User's Guide (2018), idle exhaust is calculated only for heavy-duty trucks because this process captures emissions from heavy-duty vehicles that idle for extended periods of time while loading or unloading goods.

Greenhouse Gas Emissions Calculations

Number of Annual Vehicle Trips	7008
Maximum Annual VMT	177180

Greenhouse Gas	Emission Factor Type	Emissi	ion Factor	Annual Emissions (grams/year)	Annual Emissions (MT/year)	Annual Emissions (MT of CO ₂ e/year) ¹
	RUNEX	347.7199622	grams/mile	61609022.91	61.6090	61.609
CO ₂	IDLEX ²	0	grams/vehicle/day	0.00	0.0000	0.000
CO ₂	STREX	69.56814807	grams/trip	487533.58	0.4875	0.488
				TOTAL	62.0966	62.097
	RUNEX	0.009190677	grams/mile	1628.40	0.0016	0.046
CH₄	IDLEX ²	0	grams/vehicle/day	0.00	0.0000	0.000
CH ₄	STREX	0.094267904	grams/trip	660.63	0.0007	0.018
				TOTAL	0.0023	0.064
	RUNEX	0.010901858	grams/mile	1931.59	0.0019	0.512
N ₂ O	IDLEX ²	0	grams/vehicle/day	0.00	0.0000	0.000
1420	STREX	0.033168688	grams/trip	232.45	0.0002	0.062
				TOTAL	0.0022	0.573
CO₂e					TOTAL	62.734

Notes

VMT = vehicle miles traveled; CO_2 = carbon dioxide; CH_4 = methane; N_2O = nitrous oxide; CO_2e = carbon dioxide equivalents; MT = metric tons; RUNEX = RUNEX =

Emissions factor source: California Air Resources Board EMFAC2017 Web Database v. 1.0.2 Emission Rates for Monterey County for year 2020 for gasoline-fueled LDT1 vehicles.

Global warming potentials for CH₄ and N₂O source: Intergovernmental Panel for Climate Change (2015) Climate Change 2014 Synthesis Report.

More information on emission factors can be found in the EMFAC2017 Volume I - User's Guide (2018) available at: https://ww3.arb.ca.gov/msei/downloads/emfac2017-volume-i-users-guide-final.pdf

 $^{^{1}}$ Assumes a global warming potential of 28 for CH₄ and 265 for N₂O.

² According to the CARB EMFAC 2017 Volume 1 - User's Guide (2018), idle exhaust is calculated only for heavy-duty trucks because this process captures emissions from heavy-duty vehicles that idle for extended periods of time while loading or unloading goods.

Source: EMFAC2017 (v1.0.2) Emission Rates

Region Type: County Region: Monterey Calendar Year: 2020 Season: Annual

Vehicle Classification: EMFAC2011 Categories

Units: miles/day for VMT, trips/day for Trips, g/mile for RUNEX, PMBW and PMTW, g/trip for STREX, HOTSOAK and RUNLOSS, g/vehicle/day for IDLEX,

RESTLOSS and DIURN

Calendar Year	2020
Vehicle Category	LDT1
Model Year	Aggregate
Speed	Aggregate
Fuel	Gasoline
Population	15883.36119
VMT	560231.4269
Trips	72353.65478
NOx_RUNEX	0.152815038
NOx_IDLEX	0
NOx_STREX	0.329095635
PM2.5_RUNEX	0.00260495
PM2.5_IDLEX	0
PM2.5_STREX	0.002689121
PM2.5_PMTW	0.002000001
PM2.5_PMBW	0.015750005
PM10_RUNEX	0.00283291
PM10_IDLEX	0
PM10_STREX	0.002924334
PM10_PMTW	0.008000002
PM10_PMBW	0.036750011
CO2_RUNEX	347.7199622
CO2_IDLEX	0
CO2_STREX	69.56814807
CH4_RUNEX	0.009190677
CH4_IDLEX	0
CH4_STREX	0.094267904
N2O_RUNEX	0.010901858
N2O_IDLEX	0
N2O_STREX	0.033168688
ROG_RUNEX	0.041275223
ROG_IDLEX	0
ROG_STREX	0.490113042
ROG_HOTSOAK	0.237161457
ROG_RUNLOSS	0.865214339
ROG_RESTLOSS	0.387310273

0.473624501
0.060175125
0
0.536607339
0.237161457
0.865214339
0.387310273
0.473624501
1.620705972
0
2.825834995
0.003440971
0
0.000688433

Last Updated: June 4, 2020

Populate one of the following tables (Leave the other blank):					
Annual VMT OR Daily Vehicle Trips					
Appual VMT: 177 190		Daily Vehicle			
Annual VMT: 177,180		Trips:			
	-	Average Trip			
		Distance:			

Fleet Class	Fleet Mix	Fuel Economy (MPG)
Light Duty Auto (LDA)	0.000000	Passenger Vehicles	24.0
Light Duty Truck 1 (LDT1)	1.000000	Light-Med Duty Trucks	17.4
Light Duty Truck 2 (LDT2)	0.000000	Heavy Trucks/Other	7.4
Medium Duty Vehicle (MDV)	0.000000	Motorcycles	43.9
Light Heavy Duty 1 (LHD1)	0.000000		
Light Heavy Duty 2 (LHD2)	0.000000		
Medium Heavy Duty (MHD)	0.000000		
Heavy Heavy Duty (HHD)	0.000000		
Other Bus (OBUS)	0.000000		
Urban Bus (UBUS)	0.000000		
School Bus (SBUS)	0.000000		
Motorhome (MH)	0.000000		
Motorcycle (MCY)	0.000000		

	Fuel				
			Annual VMT:		Consumption
Vehicle Type	Percent	Fuel Type	VMT	Vehicle Trips: VMT	(Gallons)
Passenger Vehicles	0.00%	Gasoline	0	0.00	0.00
Light-Medium Duty Trucks	100.00%	Gasoline	177180	0.00	10182.76
Heavy Trucks/Other	0.00%	Diesel	0	0.00	0.00
Motorcycle	0.00%	Gasoline	0	0.00	0.00

Total Gasoline Consumption (gallons)	10182.76
Total Diesel Consumption (gallons)	0.00

3 6/4/2020 4:52 PM

GHG Emission Reduction Measure - Teleworking

Number of Employees	
Teleworking	15
Number of Days per Week for	
Teleworking	2
Number of Annual Vehicle Trips	1560
Maximum Annual VMT ¹	33696

Greenhouse Gas	Emission Factor Type	Emissi	on Factor	Annual Emissions (grams/year)	Annual Emissions (MT/year)	Annual Emissions (MT of CO ₂ e/year) ²
	RUNEX	298.5998476	grams/mile	10061620.47	10.0616	10.062
CO ₂	IDLEX ³	0	grams/vehicle/day	0.00	0.0000	0.000
202	STREX	59.85430507	grams/trip	93372.72	0.0934	0.093
				TOTAL	10.1550	10.155
	RUNEX	0.005093446	grams/mile	171.63	0.0002	0.005
CH₄	IDLEX ³	0	grams/vehicle/day	0.00	0.0000	0.000
C114	STREX	0.073722737	grams/trip	115.01	0.0001	0.003
				TOTAL	0.0003	0.008
	RUNEX	0.006704133	grams/mile	225.90	0.0002	0.060
N ₂ O	IDLEX ³	0	grams/vehicle/day	0.00	0.0000	0.000
1420	STREX	0.030307244	grams/trip	47.28	0.0000	0.013
				TOTAL	0.0003	0.072
CO₂e					TOTAL	10.235

Notes

VMT = vehicle miles traveled; CO_2 = carbon dioxide; CH_4 = methane; N_2O = nitrous oxide; CO_2e = carbon dioxide equivalents; MT = metric tons; RUNEX = Running Exhaust Emissions; IDLEX = Ide Exhaust Emissions (calculated only for heavy-duty trucks; STREX = Start Exhaust Tailpipe Emissions

¹ Assumes a one-way commute distance of 10.8 miles, consistent with the default home-work distance value for Monterey County used in CalEEMod.

Emissions factor source: California Air Resources Board EMFAC2017 Web Database v. 1.0.2 Emission Rates for Monterey County for year 2020 for gasoline-fueled LDA vehicles.

Global warming potentials for CH_4 and N_2O source: Intergovernmental Panel for Climate Change (2015) Climate Change 2014 Synthesis Report.

More information on emission factors can be found in the EMFAC2017 Volume I - User's Guide (2018) available at:

https://ww3.arb.ca.gov/msei/downloads/emfac2017-volume-i-users-guide-final.pdf

 $^{^2}$ Assumes a global warming potential of 28 for $\mathrm{CH_4}$ and 265 for $\mathrm{N_2O}$.

³ According to the CARB EMFAC 2017 Volume 1 - User's Guide (2018), idle exhaust is calculated only for heavy-duty trucks because this process captures emissions from heavy-duty vehicles that idle for extended periods of time while loading or unloading goods.

GHG Emission Reduction Measure - Subsidizing Transit Passes

-	
Number of Employees with	
Transit Passes	6
Number of Days per Week using	
Transit	3
Number of Annual Vehicle Trips	936
Maximum Annual VMT ¹	20217.6

Greenhouse Gas	Emission Factor Type	Emission Factor A		Annual Emissions (grams/year)	Annual Emissions (MT/year)	Annual Emissions (MT of CO ₂ e/year) ²
	RUNEX	298.5998476	grams/mile	6036972.28	6.0370	6.037
CO ₂	IDLEX ³	0	grams/vehicle/day	0.00	0.0000	0.000
	STREX	59.85430507	grams/trip	56023.63	0.0560	0.056
				TOTAL	6.0930	6.093
	RUNEX	0.005093446	grams/mile	102.98	0.0001	0.003
CH₄	IDLEX ³	0	grams/vehicle/day	0.00	0.0000	0.000
C114	STREX	0.073722737	grams/trip	69.00	0.0001	0.002
			0.0002	0.005		
	RUNEX	0.006704133	grams/mile	135.54	0.0001	0.036
N ₂ O	IDLEX ³	0	grams/vehicle/day	0.00	0.0000	0.000
1420	STREX	0.030307244	grams/trip	28.37	0.0000	0.008
	TOTAL 0.0002					0.043
CO₂e		6.141				

Notes

VMT = vehicle miles traveled; CO_2 = carbon dioxide; CH_4 = methane; N_2O = nitrous oxide; CO_2e = carbon dioxide equivalents; MT = metric tons; RUNEX = Running Exhaust Emissions; IDLEX = Ide Exhaust Emissions (calculated only for heavy-duty trucks; STREX = Start Exhaust Tailpipe Emissions

¹ Assumes a one-way commute distance of 10.8 miles, consistent with the default home-work distance value for Monterey County used in CalEEMod.

 2 Assumes a global warming potential of 28 for $\mathrm{CH_4}$ and 265 for $\mathrm{N_2O}$.

³ According to the CARB EMFAC 2017 Volume 1 - User's Guide (2018), idle exhaust is calculated only for heavy-duty trucks because this process captures emissions from heavy-duty vehicles that idle for extended periods of time while loading or unloading goods.

Emissions factor source: California Air Resources Board EMFAC2017 Web Database v. 1.0.2 Emission Rates for Monterey County for year 2020 for gasoline-fueled LDA vehicles.

Global warming potentials for CH_4 and N_2O source: Intergovernmental Panel for Climate Change (2015) Climate Change 2014 Synthesis Report.

More information on emission factors can be found in the EMFAC2017 Volume I - User's Guide (2018) available at:

https://ww3.arb.ca.gov/msei/downloads/emfac2017-volume-i-users-guide-final.pdf

MPWMD Potential Acquisition of Monterey Water Supply and District Boundary Adjustment GHG Emission Reduction Measure - EV Conversion Reduction

Number of Vehicles Converted	3
Number of Annual Vehicle Trips	2964
Maximum Annual VMT ¹	118560

Greenhouse Gas	Emission Factor Type	Emission Factor	Annual Emissions (grams/year)	Annual Emissions (MT/year)	Annual Emissions (MT of CO ₂ e/year) ²
	RUNEX	298.5998476 grams/mile	35401997.94	35.4020	35.402
CO ₂	IDLEX ³	0 grams/vehicle/day	0.00	0.0000	0.000
CO ₂	STREX	59.85430507 grams/trip	177408.16	0.1774	0.177
			TOTAL	35.5794	35.579
	RUNEX	0.005093446 grams/mile	603.88	0.0006	0.017
CH ₄	IDLEX ³	0 grams/vehicle/day	0.00	0.0000	0.000
CH ₄	STREX	0.073722737 grams/trip	218.51	0.0002	0.006
			TOTAL	0.0008	0.023
	RUNEX	0.006704133 grams/mile	794.84	0.0008	0.211
N ₂ O	IDLEX ³	0 grams/vehicle/day	0.00	0.0000	0.000
1420	STREX	0.030307244 grams/trip	89.83	0.0001	0.024
			TOTAL	0.0009	0.234
CO₂e				TOTAL	35.837

MBCP Emissions Factors							
	Carbon Intensity Factors (lb/MWh)	Emissions Factors (MT CO2e/MWh)					
CO2e	2	0.00091					


		EV Usage	
Level 2 Charger	6.6	kW	Notes
4 Hour Charge	26.4	kWh	

Project Report - i-Tree Planting Calculator_{v2.1.0}

Location: Pacific Grove, California 93950

Electricity Emissions Factor: 2.00 pounds CO2 equivalent/MWh Fuel Emissions Factor: 52.00 kilograms CO2 equivalent/MMBtu

Lifetime: 40 years Tree Mortality: 10%



Location		CO ₂ (Carbon Dioxide) Benefits				
Group Identifier	Tree Group Characteristics	CO ₂ (Carbon Dioxide) Avoided (pounds)	CO ₂ Avoided (\$)	CO ₂ Sequestered (pounds)	CO ₂ Sequestered (\$)	
1	 (1.0) Boxelder (Acer negundo) at 1.0 inch <u>DBH (Diameter at Breast Height)</u>. Planted 0-19 feet and north (0°) of buildings that were built post-1980 with heat and A/C. Trees are in excellent condition and planted in partial sun. 	742.9	\$17.28	7,299.9	\$169.77	



Location		Energy Benefits				
Group Identifier	Tree Group Characteristics	Electricity Saved (kWh) (Kilowatt- Hours)	Electricity Saved (\$)	Fuel Saved (MMBtu) (Millions of British Thermal Units)	Fuel Saved (\$)	
1	 (1.0) Boxelder (Acer negundo) at 1.0 inch DBH (Diameter at Breast Height). Planted 0-19 feet and north (0°) of buildings that were built post-1980 with heat and A/C. Trees are in excellent condition and planted in partial sun. 	2,003.9	\$398.78	6.4	\$83.36	

Location		Ecosystem Services				
Group Identifier	Tree Group Characteristics	Tree Biomass (short ton)	Rainfall Interception (gallons)	Runoff Avoided (gallons)	Runoff Avoided (\$)	
1	 (1.0) Boxelder (Acer negundo) at 1.0 inch <u>DBH (Diameter at Breast Height)</u>. Planted 0-19 feet and north (0°) of buildings that were built post-1980 with heat and A/C. Trees are in excellent condition and planted in partial sun. 	1.9	32,141.4	7,064.1	\$63.12	

Location		Air Benefit	ts						
Group Identifier	Tree Group Characteristics	O ₃ (Ozone) Removed (pounds)	NO ₂ (Nitrogen Dioxide) Avoided (pounds)	NO ₂ (Nitrogen Dioxide) Removed (pounds)	SO ₂ (Sulfur Dioxide) Avoided (pounds)	SO ₂ (Sulfur Dioxide) Removed (pounds)	VOC (Volatile Organic Compound) Avoided (pounds)	PM _{2.5} (Particulate matter smaller than 2.5 micrometers in diameter) Avoided (pounds)	PM _{2.5} (Particulate matter smaller than 2.5 micrometers in diameter) Removed (pounds)
1	 (1.0) Boxelder (Acer negundo) at 1.0 inch <u>DBH</u> (Diameter at Breast <u>Height</u>). Planted 0-19 feet and north (0°) of buildings that were built post-1980 with heat and A/C. Trees are in excellent condition and planted in partial sun. 	20.3	0.1	1.1	0.5	0.2	1.0	0.7	0.1

















www.fs.fed.us
www.davey.com
www.arborday.org
www.urban-forestry.com
www.isa-arbor.com
www.caseytrees.org
www.esf.edu
www.northeasternforests.org

Use of this tool indicates acceptance of the End-User License Agreement (EULA), which can be found at: https://help.itreetools.org/eula